

HiDM

HIGH DENSITY MONO PERC MODULE

320 W ~ 335 W




CS1K-320 | 325 | 330 | 335MS

Dimensions: 1675 × 992 × 35 mm (65.9 × 39.1 × 1.38 in)




Max. System Voltage: 1000 V (IEC) or 1000 V (UL)

Weight: 18.5 kg (40.8 lbs)

MORE POWER

-  Maximize the light absorption area, module efficiency up to 20.16 %
-  Low NMOT: 42 ± 3 °C
Low temperature coefficient (Pmax): -0.37 % / °C
-  Innovative module design, better shading tolerance

MORE RELIABLE

-  Lower internal current, lower hot spot temperature
-  Cell crack risk limited in small region, enhance the module reliability
-  Heavy snow load up to 5400 Pa, wind load up to 2400 Pa



linear power output warranty



product warranty on materials and workmanship

PRODUCT CERTIFICATES*

IEC 61215 / IEC 61730: VDE / CE (Expected on August, 2018)

UL 1703: CSA (Expected on September, 2018)

* If you need specific product certificates, and if module installations are to deviate from our guidance specified in our installation manual, please contact your local Canadian Solar sales and technical representatives.

CANADIAN SOLAR INC. is committed to providing high quality solar products, solar system solutions and services to customers around the world. As a leading PV project developer and manufacturer of solar modules with about 30 GW deployed around the world since 2001, Canadian Solar Inc. is one of the most bankable solar companies worldwide.