

Assembled in/Assemblé au
CANADA 

HiDM HIGH DENSITY MONO PERC MODULE

320 W ~ 345 W

CS1H-320 | 325 | 330 | 335 | 340 | 345MS

MORE POWER



Maximize the light absorption area,
module efficiency up to 20.46 %



Low temperature coefficient (Pmax):
-0.37 % / °C



Better shading tolerance

MORE RELIABLE



Lower internal current,
lower hot spot temperature



Cell crack risk limited in small region,
enhance the module reliability



Heavy snow load up to 5400 Pa,
wind load up to 2400 Pa*



15 years enhanced product warranty on materials
and workmanship*



25 years linear power output warranty*

*According to the applicable Canadian Solar Limited Warranty Statement.

MANAGEMENT SYSTEM CERTIFICATES*

ISO 9001:2015 / Quality management system

ISO 14001:2015 / Standards for environmental management system

OHSAS 18001:2007 / International standards for occupational health & safety

PRODUCT CERTIFICATES*

IEC 61215 / IEC 61730: VDE / CE / MCS / JET / INMETRO

UL 1703 / IEC 61215 performance: CEC listed (US) / FSEC (US Florida)

UL 1703: CSA / IEC 61701 ED2: VDE / IEC 62716: VDE

UNI 9177 Reaction to Fire: Class 1 / Take-e-way



As there are different certification requirements in different markets, please contact your local Canadian Solar sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

CANADIAN SOLAR SOLUTIONS is committed to providing high quality solar products, solar system solutions and services to customers around the world. No. 1 module supplier for quality and performance/price ratio in IHS Module Customer Insight Survey. As a leading PV project developer and manufacturer of solar modules with over 40 GW deployed around the world since 2001.


* For detail information, please refer to Installation Manual.

CANADIAN SOLAR SOLUTIONS


545 Speedvale Avenue West, Guelph, Ontario N1K 1E6, Canada, www.canadiansolar.com, support@canadiansolar.com

ENGINEERING DRAWING (mm)


Rear View




Frame Cross Section A-A



Mounting Hole



CS1H-330MS / I-V CURVES



ELECTRICAL DATA | STC*

CS1H	320MS	325MS	330MS	335MS	340MS	345MS
Nominal Max. Power (Pmax)	320 W	325 W	330 W	335 W	340 W	345 W
Opt. Operating Voltage (Vmp)	36.2 V	36.6 V	37.0 V	37.4 V	37.8 V	38.2 V
Opt. Operating Current (Imp)	8.85 A	8.88 A	8.92 A	8.96 A	9.00 A	9.04 A
Open Circuit Voltage (Voc)	44.0 V	44.1 V	44.2 V	44.3 V	44.5 V	44.6 V
Short Circuit Current (Isc)	9.41 A	9.45 A	9.49 A	9.53 A	9.57 A	9.61 A
Module Efficiency	19.0%	19.3%	19.6%	19.9%	20.2%	20.5%
Operating Temperature	-40°C ~ +85°C					
Max. System Voltage	1500V (IEC) or 1000V (IEC/UL)					
Module Fire Performance	TYPE 1 (UL 1703) or CLASS C (IEC 61730)					
Max. Series Fuse Rating	15 A					
Application Classification	Class A					
Power Tolerance	0 ~ + 10 W					

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

ELECTRICAL DATA | NMOT*

CS1H	320MS	325MS	330MS	335MS	340MS	345MS
Nominal Max. Power (Pmax)	237 W	241 W	244 W	248 W	252 W	255 W
Opt. Operating Voltage (Vmp)	33.5 V	33.9 V	34.2 V	34.6 V	35.0 V	35.3 V
Opt. Operating Current (Imp)	7.07 A	7.11 A	7.14 A	7.17 A	7.20 A	7.23 A
Open Circuit Voltage (Voc)	41.1 V	41.2 V	41.3 V	41.4 V	41.6 V	41.7 V
Short Circuit Current (Isc)	7.6 A	7.63 A	7.66 A	7.69 A	7.72 A	7.76 A

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m² spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Canadian Solar Inc. reserves the right to make necessary adjustment to the information described herein at any time without further notice. Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills and please carefully read the safety and installation instructions before using our PV modules.

MECHANICAL DATA

Specification	Data
Cell Type	Mono-crystalline
Dimensions	1700 × 992 × 35 mm (66.9 × 39.1 × 1.38 in)
Weight	19.2 kg (42.3 lbs)
Front Cover	3.2 mm tempered glass
Frame	Anodized aluminium alloy
J-Box	IP68, 3 bypass diodes
Cable	4.0 mm² (IEC), 12 AWG (UL)
Cable Length	1350 mm (53.1 in) (Including Connector)
Connector	T4 series
Per Pallet	30 pieces
Per Container (40' HQ)	780 pieces

TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.37 % / °C
Temperature Coefficient (Voc)	-0.29 % / °C
Temperature Coefficient (Isc)	0.05 % / °C
Nominal Module Operating Temperature	43±3 °C

PARTNER SECTION

